Desktop Mono Laser Printers

RICOH imagine. change.

RICOH SP 230DNw SP 230SFNw







Compact and Robust

The SP 230 series are A4, Mono laser printers providing print speed up to 30 pages per minute (ppm). The SP 230DNw is a single function printer while the SP 230SFNw is a multifunction printer (MFP) providing copy, print, scan, and fax functions.

The devices provide high-quality prints at 1200×1200 dpi resolution, automatic duplex printing, and support for $60 - 230 \text{ g/m}^2$ paper weights. The support for Windows, Macintosh, and Linux operating systems ensure that the devices can be used in a wide variety of workplaces.

The SP 230DNw and SP 230SFNw come with Wi-Fi Direct connectivity as standard and are Google Cloud Print-ready, which allows any smart device or PC with a cloud-aware application to print to the devices. Direct mobile printing from Android and Apple devices are also supported via Mopria and AirPrint standards respectively.

Additionally, the devices are compact in size and provide quiet operation, leading to greater efficiency and user productivity especially in smaller office environments.



Productivity at 30ppm

The SP 230 series provides crisp and clear output at 1200 x 1200 dpi resolution, which makes them ideal for business use without straining the budget.

Support for 60-230 g/m² paper weights as well as envelopes enable customers to print a wider variety of applications in-house.



Enable your mobile workforce

Easy mobile printing via Wi-Fi Direct, Mopria, AirPrint and Google Cloud Print. No longer locked down to your desk, print on the go, anytime, anywhere.

The SP 230 series come with standard duplex for mono printing and color scanning, boosting your work efficiency.



Environment conscious

SP 230 series features quiet operation that is beneficial for placement in small rooms.

Reduce paper costs with default duplex print. Cut energy costs with Sleep Mode when device is inactive.

These devices are compliant with the industry-leading Energy Star energy saving standard.



RICOH SP 230DNw / SP 230SFNw

MAIN SPECIFICATIONS

MODEL	SP 230DNw	SP 230SFNw
GENERAL		
Configuration	Desktop Legar (Mana)	
Гесhnology	Laser ((Mono)
unctions	Print	Print, Copy, Scan, Fax
Display	1 line LCD	2 line LCD
Processor	600	MHz
Memory	128 MB	256 MB
Mobile Capability	Airprint, Google C	loud Print, Mopria
Printer Language	GDI	
nterface	Ethernet 10Base-T / 100Base-TX, IEEE802.11b/g/n, USB 2.0	
Network Protocol	TCP/IP	
Operating System	Windows 7/8.1/10, Windows Server 2008/2012/2012 R2/ 2016, MAC OS X10.11 - 10.13, Redhat Enterprise7 x64, Fedora24x32, Fedora25x64, Mageia5 x64, openSUSE13.2 x32, openSUSE42.2 x64, SUSE Enterprise12.2 x64, Debian8.3.0 x32, Debian8.3.0 x64, Ubuntu17.04 x32, Ubuntu17.04x64, Ubuntu17.10x64, LinuxMint18 x32, LinuxMint18 x64, Ubuntu14.04 x64	
PRINT		
Duplex Printing	Au	uto
Print Speed (A4)	30 ppm (Simplex).	7.5 ppm (Duplex)
First Print Out Time		nds or less
Warm Up time	28 seconds or less	
variii op tillie		
Print Resolution	600 x 600 dpi (Default) 300 x 300 dpi, 600 x 600 dpi, 1,200 x 1,200 dpi, 2,400 x 600 dpi	
Average Print Value -		
Average Print Volume	400 - 1,000 pages	400 - 1,000 pages
Outy Cycle	15,000 pa	ges/month
COPY		
Copy Speed (A4)	-	Up to 30 ppm
Document Feeder Type	-	Automatic Document Feeder
Document Feeder Capacity	-	50
Resolution	-	600 x 600 dpi (ADF), 1,200 x 1,200 dpi (Platen)
Multiple Copy	-	Up to 99
		Zoom Range: 25%-400%, Image Quality: Auto/Text/Photo/Receipt,
Copy Features	-	Image Density: 5 levels, ID Card Copy
SCAN		image bensity. 3 levels, ib card copy
CAN		
ican Speed (A4 ADF)	-	Mono: 22.5 impressions/minute, Color: 7.5 impressions/minute
Resolution	-	600 x 600 dpi (ADF)
		1,200 x 1,200 dpi (Platen)
Original Size	-	A4
Bundled Drivers	-	Network TWAIN
Bundled Drivers Scan To		Network TWAIN
Bundled Drivers Scan To FAX	-	Network TWAIN Scan to folder, Scan to searchable PDF, Scan to PDF/A, TWAIN scanning
Bundled Drivers Scan To	-	Network TWAIN
Bundled Drivers Scan To FAX	- - PSTN	Network TWAIN Scan to folder, Scan to searchable PDF, Scan to PDF/A, TWAIN scanning
Bundled Drivers Scan To AX Circuit Compatibility	- - PSTN V34 (Su	Network TWAIN Scan to folder, Scan to searchable PDF, Scan to PDF/A, TWAIN scanning , PBX
Bundled Drivers Scan To SAX Circuit	- - PSTN V34 (Su Horizontal: 203	Network TWAIN Scan to folder, Scan to searchable PDF, Scan to PDF/A, TWAIN scanning , PBX uper G3)
Bundled Drivers Scan To AX Circuit Compatibility	- PSTN V34 (Su Horizontal: 203 Vertical 98 dpi-3.85dots/mm, 196 dp	Network TWAIN Scan to folder, Scan to searchable PDF, Scan to PDF/A, TWAIN scanning , PBX per G3) 8 dpi-8dots/mm,
Bundled Drivers GCAN GCAN Circuit Compatibility Resolution Transmission Speed	- PSTN V34 (Su Horizontal: 203 Vertical 98 dpi-3.85dots/mm, 196 dp 33.6 Kbps with au	Network TWAIN Scan to folder, Scan to searchable PDF, Scan to PDF/A, TWAIN scanning , PBX per G3) dipi-8dots/mm, pi-7.7dots/mm, 392 dpi-15.4dots/mm
Bundled Drivers Gran To FAX Circuit Compatibility Resolution Fransmission Speed Compression Method	- PSTN V34 (Su Horizontal: 203 Vertical 98 dpi-3.85dots/mm, 196 dp 33.6 Kbps with au MH, MR, I	Network TWAIN Scan to folder, Scan to searchable PDF, Scan to PDF/A, TWAIN scanning , PBX pper G3) dipi-8dots/mm, pi-7.7dots/mm, 392 dpi-15.4dots/mm tomatic shift down MMR, JBIG
Bundled Drivers Gran To FAX Circuit Compatibility Resolution Fransmission Speed	- PSTN V34 (Su Horizontal: 203 Vertical 98 dpi-3.85dots/mm, 196 dp 33.6 Kbps with au MH, MR, I Automatic, Manual, Substitute, Authorised (100 addre	Network TWAIN Scan to folder, Scan to searchable PDF, Scan to PDF/A, TWAIN scanning PBX PPER G3) G dpi-8dots/mm, pi-7.7dots/mm, 392 dpi-15.4dots/mm tomatic shift down MMR, JBIG ESSES), Time stamp printing, Toner saving mode, Duplex
Bundled Drivers Gran To FAX Circuit Compatibility Resolution Fransmission Speed Compression Method	- PSTN V34 (Su Horizontal: 203 Vertical 98 dpi-3.85dots/mm, 196 dp 33.6 Kbps with au MH, MR, I Automatic, Manual, Substitute, Authorised (100 addre	Network TWAIN Scan to folder, Scan to searchable PDF, Scan to PDF/A, TWAIN scanning , PBX per G3) dipi-8dots/mm, pi-7.7dots/mm, 392 dpi-15.4dots/mm tomatic shift down MMR, JBIG ssses), Time stamp printing, Toner saving mode, Duplex ccess, User code, Auto reduction, Summer time, User function key, Clock nal Identification (CTI), Called Subscriber Identification (CSI), All documen
Bundled Drivers Goan To FAX Circuit Compatibility Resolution Fransmission Speed Compression Method Reception Features Other Supported Features	- PSTN V34 (Su Horizontal: 203 Vertical 98 dpi-3.85dots/mm, 196 dp 33.6 Kbps with au MH, MR, I Automatic, Manual, Substitute, Authorised (100 addre	Network TWAIN Scan to folder, Scan to searchable PDF, Scan to PDF/A, TWAIN scanning , PBX uper G3) dipi-8dots/mm, pi-7.7dots/mm, 392 dpi-15.4dots/mm tomatic shift down MMR, JBIG usess), Time stamp printing, Toner saving mode, Duplex ccess, User code, Auto reduction, Summer time, User function key, Clock
Bundled Drivers Goan To FAX Circuit Compatibility Resolution Fransmission Speed Compression Method Reception Features Other Supported Features	PSTN V34 (Su Horizontal: 203 Vertical 98 dpi-3.85dots/mm, 196 dp 33.6 Kbps with au MH, MR, I Automatic, Manual, Substitute, Authorised (100 addre Memory backup, Quick dial/speed dial, Direct fax number entry, Dual ar adjustment, User parameter settings, User data transfer Transmitter Termi transfer, Double check destination address, Paperless fa	Network TWAIN Scan to folder, Scan to searchable PDF, Scan to PDF/A, TWAIN scanning , PBX per G3) dipi-8dots/mm, pi-7.7dots/mm, 392 dpi-15.4dots/mm tomatic shift down MMR, JBIG sesses), Time stamp printing, Toner saving mode, Duplex ccess, User code, Auto reduction, Summer time, User function key, Clock nal Identification (TTI), Called Subscriber Identification (CSI), All documen ix reception, Universal send—simultaneous fax and scan
Bundled Drivers Goan To FAX Circuit Compatibility Resolution Fransmission Speed Compression Method Reception Features Other Supported Features	PSTN V34 (Su Horizontal: 203 Vertical 98 dpi-3.85dots/mm, 196 dp 33.6 Kbps with au MH, MR, I Automatic, Manual, Substitute, Authorised (100 addre Memory backup, Quick dial/speed dial, Direct fax number entry, Dual ar adjustment, User parameter settings, User data transfer Transmitter Termi transfer, Double check destination address, Paperless fa	Network TWAIN Scan to folder, Scan to searchable PDF, Scan to PDF/A, TWAIN scanning , PBX per G3) dipi-8dots/mm, pi-7.7dots/mm, 392 dpi-15.4dots/mm tomatic shift down MMR, JBIG ssses), Time stamp printing, Toner saving mode, Duplex ccess, User code, Auto reduction, Summer time, User function key, Clock nal Identification (CTI), Called Subscriber Identification (CSI), All documen
Bundled Drivers Gan To FAX Circuit Compatibility Resolution Fransmission Speed Compression Method Reception Features Other Supported Features PAPER HANDLING Recommended Paper Size	PSTN V34 (Su Horizontal: 203 Vertical 98 dpi-3.85dots/mm, 196 dp 33.6 Kbps with au MH, MR, I Automatic, Manual, Substitute, Authorised (100 addre Memory backup, Quick dial/speed dial, Direct fax number entry, Dual a adjustment, User parameter settings, User data transfer Transmitter Termi transfer, Double check destination address, Paperless fa	Network TWAIN Scan to folder, Scan to searchable PDF, Scan to PDF/A, TWAIN scanning , PBX per G3) dipi-8dots/mm, pi-7.7dots/mm, 392 dpi-15.4dots/mm tomatic shift down MMR, JBIG sesses), Time stamp printing, Toner saving mode, Duplex cess, User code, Auto reduction, Summer time, User function key, Clock nal Identification (TTI), Called Subscriber Identification (CSI), All documer ix reception, Universal send—simultaneous fax and scan
Bundled Drivers Goan To FAX Circuit Compatibility Resolution Gransmission Speed Compression Method Reception Features Other Supported Features PAPER HANDLING Recommended Paper Size Paper Input Capacity	PSTN V34 (Su Horizontal: 203 Vertical 98 dpi-3.85dots/mm, 196 dp 33.6 Kbps with au MH, MR, I Automatic, Manual, Substitute, Authorised (100 addre Memory backup, Quick dial/speed dial, Direct fax number entry, Dual a adjustment, User parameter settings, User data transfer Transmitter Termi transfer, Double check destination address, Paperless fa	Network TWAIN Scan to folder, Scan to searchable PDF, Scan to PDF/A, TWAIN scanning , PBX pper G3) dipi-8dots/mm, pi-7.7dots/mm, 392 dpi-15.4dots/mm tomatic shift down MMR, JBIG ssess), Time stamp printing, Toner saving mode, Duplex ccess, User code, Auto reduction, Summer time, User function key, Clock nal Identification (TTI), Called Subscriber Identification (CSI), All documen ix reception, Universal send—simultaneous fax and scan
Bundled Drivers GCAX Circuit Compatibility Resolution Gransmission Speed Compression Method Reception Features Other Supported Features PAPER HANDLING Recommended Paper Size Paper Input Capacity Paper Output Capacity	PSTN V34 (Su Horizontal: 203 Vertical 98 dpi-3.85dots/mm, 196 dp 33.6 Kbps with au MH, MR, I Automatic, Manual, Substitute, Authorised (100 addre Memory backup, Quick dial/speed dial, Direct fax number entry, Dual a adjustment, User parameter settings, User data transfer Transmitter Termi transfer, Double check destination address, Paperless fa A4, B5(IIS), A5, 250 sheets (Bypass: 1shee	Network TWAIN Scan to folder, Scan to searchable PDF, Scan to PDF/A, TWAIN scanning , PBX pper G3) dipi-8dots/mm, pi-7.7dots/mm, 392 dpi-15.4dots/mm tomatic shift down MMR, JBIG sesses), Time stamp printing, Toner saving mode, Duplex ccess, User code, Auto reduction, Summer time, User function key, Clock nal Identification (TTI), Called Subscriber Identification (CSI), All documen ax reception, Universal send—simultaneous fax and scan A6, LT, Executive at), Maximum: 251 sheets
Bundled Drivers GCAX Circuit Compatibility Resolution Gransmission Speed Compression Method Reception Features Other Supported Features PAPER HANDLING Recommended Paper Size Paper Input Capacity Paper Output Capacity Paper Weight	PSTN V34 (Su Horizontal: 203 Vertical 98 dpi-3.85dots/mm, 196 dp 33.6 Kbps with au MH, MR, I Automatic, Manual, Substitute, Authorised (100 addre Memory backup, Quick dial/speed dial, Direct fax number entry, Dual a adjustment, User parameter settings, User data transfer Transmitter Termi transfer, Double check destination address, Paperless fa A4, B5(IIS), A5, 250 sheets (Bypass: 1shee	Network TWAIN Scan to folder, Scan to searchable PDF, Scan to PDF/A, TWAIN scanning , PBX dip-8 dots/mm, pi-7.7dots/mm, 392 dpi-15.4dots/mm tomatic shift down MMR, JBIG sses), Time stamp printing, Toner saving mode, Duplex ccess, User code, Auto reduction, Summer time, User function key, Clock nal Identification (TTI), Called Subscriber Identification (CSI), All documer ix reception, Universal send—simultaneous fax and scan A6, LT, Executive et), Maximum: 251 sheets
Bundled Drivers GCAX Circuit Compatibility Resolution Gransmission Speed Compression Method Reception Features Other Supported Features PAPER HANDLING Recommended Paper Size Paper Input Capacity Paper Output Capacity Paper Weight ECOLOGY	PSTN V34 (Su Horizontal: 203 Vertical 98 dpi-3.85dots/mm, 196 dp 33.6 Kbps with au MH, MR, I Automatic, Manual, Substitute, Authorised (100 addre Memory backup, Quick dial/speed dial, Direct fax number entry, Dual a adjustment, User parameter settings, User data transfer Transmitter Termi transfer, Double check destination address, Paperless fa A4, B5(IIS), A5, 250 sheets (Bypass: 1sheet 150 sheets	Network TWAIN Scan to folder, Scan to searchable PDF, Scan to PDF/A, TWAIN scanning , PBX dip-8dots/mm, pi-7.7dots/mm, 392 dpi-15.4dots/mm tomatic shift down MMR, JBIG sses), Time stamp printing, Toner saving mode, Duplex ccess, User code, Auto reduction, Summer time, User function key, Clock nal Identification (TTI), Called Subscriber Identification (CSI), All documer ix reception, Universal send—simultaneous fax and scan A6, LT, Executive et), Maximum: 251 sheets 120 sheets lass: 60 to 230 g/m²)
Bundled Drivers GCAX Circuit Compatibility Resolution GCAX Compression Method Reception Features Other Supported Features COMPANDLING Recommended Paper Size Compared Input Capacity Compared Weight Coology C	PSTN V34 (Su Horizontal: 203 Vertical 98 dpi-3.85dots/mm, 196 dp 33.6 Kbps with au MH, MR, I Automatic, Manual, Substitute, Authorised (100 addre Memory backup, Quick dial/speed dial, Direct fax number entry, Dual a adjustment, User parameter settings, User data transfer Transmitter Termi transfer, Double check destination address, Paperless fa A4, B5(IIS), A5, 250 sheets (Bypass: 1sheet 150 sheets 60 to 163 g/m² (Bypass)	Network TWAIN Scan to folder, Scan to searchable PDF, Scan to PDF/A, TWAIN scanning , PBX , PBX , PBX , PBS a dpi-8dots/mm, pi-7.7dots/mm, 392 dpi-15.4dots/mm tomatic shift down MMR, JBIG , SSSS, Time stamp printing, Toner saving mode, Duplex , Cocess, User code, Auto reduction, Summer time, User function key, Clock nal Identification (TTI), Called Subscriber Identification (CSI), All documer ix reception, Universal send—simultaneous fax and scan A6, LT, Executive et), Maximum: 251 sheets 120 sheets ass: 60 to 230 g/m²)
Bundled Drivers Gran To FAX Circuit Compatibility Resolution Fransmission Speed Compression Method Reception Features Other Supported Features PAPER HANDLING Recommended Paper Size Paper Input Capacity Paper Output Capacity Paper Weight COLOGY Dimensions (W x D x H) Weight	PSTN V34 (Su Horizontal: 203 Vertical 98 dpi-3.85dots/mm, 196 dp 33.6 Kbps with au MH, MR, I Automatic, Manual, Substitute, Authorised (100 addre Memory backup, Quick dial/speed dial, Direct fax number entry, Dual a adjustment, User parameter settings, User data transfer Transmitter Termi transfer, Double check destination address, Paperless fa A4, B5(IIS), A5, 250 sheets (Bypass: 1sheet 150 sheets 60 to 163 g/m² (Byp 356 mm x 361 mm x 183 mm Less than 7.3 kg	Network TWAIN Scan to folder, Scan to searchable PDF, Scan to PDF/A, TWAIN scanning , PBX uper G3) dipi-8dots/mm, bi-7.7dots/mm, 392 dpi-15.4dots/mm tomatic shift down MMR, JBIG usses), Time stamp printing, Toner saving mode, Duplex ccess, User code, Auto reduction, Summer time, User function key, Clock nal Identification (TTI), Called Subscriber Identification (CSI), All documer ix reception, Universal send—simultaneous fax and scan A6, LT, Executive at), Maximum: 251 sheets 120 sheets ass: 60 to 230 g/m²) 401 mm x 399 mm x 318 mm Less than 11.8 kg
Bundled Drivers Gran To AX Circuit Compatibility Resolution Transmission Speed Compression Method Reception Features Other Supported Features PAPER HANDLING Recommended Paper Size Paper Input Capacity Paper Output Capacity Paper Weight COLOGY Dimensions (W x D x H) Weight Power Consumption (Max)	PSTN V34 (Su Horizontal: 203 Vertical 98 dpi-3.85dots/mm, 196 dp 33.6 Kbps with au MH, MR, I Automatic, Manual, Substitute, Authorised (100 addre Memory backup, Quick dial/speed dial, Direct fax number entry, Dual a adjustment, User parameter settings, User data transfer Transmitter Termi transfer, Double check destination address, Paperless fa A4, B5(JIS), A5, 250 sheets (Bypass: 1sheet 150 sheets 60 to 163 g/m² (Bypass) 356 mm x 361 mm x 183 mm Less than 7.3 kg 1,104 V	Network TWAIN Scan to folder, Scan to searchable PDF, Scan to PDF/A, TWAIN scanning , PBX pper G3) 8 dpi-8dots/mm, pi-7.7dots/mm, 392 dpi-15.4dots/mm tomatic shift down MMR, JBIG sses), Time stamp printing, Toner saving mode, Duplex ccess, User code, Auto reduction, Summer time, User function key, Clock nal Identification (TTI), Called Subscriber Identification (CSI), All documer ix reception, Universal send—simultaneous fax and scan A6, LT, Executive at), Maximum: 251 sheets 120 sheets ass: 60 to 230 g/m²) 401 mm x 399 mm x 318 mm Less than 11.8 kg
Bundled Drivers GCAX Circuit Compatibility Resolution Fransmission Speed Compression Method Reception Features Other Supported Features PAPER HANDLING Recommended Paper Size Paper Input Capacity Paper Output Capacity Paper Weight COLOGY Dimensions (W x D x H) Weight Power Consumption (Max)	PSTN V34 (Su Horizontal: 203 Vertical 98 dpi-3.85dots/mm, 196 dp 33.6 Kbps with au MH, MR, I Automatic, Manual, Substitute, Authorised (100 addre Memory backup, Quick dial/speed dial, Direct fax number entry, Dual a adjustment, User parameter settings, User data transfer Transmitter Termi transfer, Double check destination address, Paperless fa A4, B5(JIS), A5, 250 sheets (Bypass: 1sheet 150 sheets 60 to 163 g/m² (Byp 356 mm x 361 mm x 183 mm Less than 7.3 kg 1,104 V	Network TWAIN Scan to folder, Scan to searchable PDF, Scan to PDF/A, TWAIN scanning , PBX pper G3) 8 dpi-8dots/mm, oi-7.7dots/mm, 392 dpi-15.4dots/mm tomatic shift down MMR, JBIG sesse), Time stamp printing, Toner saving mode, Duplex ccess, User code, Auto reduction, Summer time, User function key, Clock nal Identification (TTI), Called Subscriber Identification (CSI), All documer ix reception, Universal send—simultaneous fax and scan A6, LT, Executive et), Maximum: 251 sheets 120 sheets ass: 60 to 230 g/m²) 401 mm x 399 mm x 318 mm Less than 11.8 kg V or less
Bundled Drivers GCAX Circuit Compatibility Resolution Fransmission Speed Compression Method Reception Features Other Supported Features PAPER HANDLING Recommended Paper Size Paper Input Capacity Paper Output Capacity Paper Weight COLOGY Dimensions (W x D x H) Weight Power Consumption (Max) Ready Mode	PSTN V34 (Su Horizontal: 203 Vertical 98 dpi-3.85dots/mm, 196 dp 33.6 Kbps with au MH, MR, I Automatic, Manual, Substitute, Authorised (100 addre Memory backup, Quick dial/speed dial, Direct fax number entry, Dual a adjustment, User parameter settings, User data transfer Transmitter Termi transfer, Double check destination address, Paperless fa A4, B5(JIS), A5, 250 sheets (Bypass: 1sheet 150 sheets 60 to 163 g/m² (Bypass) 356 mm x 361 mm x 183 mm Less than 7.3 kg 1,104 V	Network TWAIN Scan to folder, Scan to searchable PDF, Scan to PDF/A, TWAIN scanning , PBX pper G3) 8 dpi-8dots/mm, pi-7.7dots/mm, 392 dpi-15.4dots/mm tomatic shift down MMR, JBIG sses), Time stamp printing, Toner saving mode, Duplex ccess, User code, Auto reduction, Summer time, User function key, Clock nal Identification (TTI), Called Subscriber Identification (CSI), All documer ix reception, Universal send—simultaneous fax and scan A6, LT, Executive at), Maximum: 251 sheets 120 sheets ass: 60 to 230 g/m²) 401 mm x 399 mm x 318 mm Less than 11.8 kg
Bundled Drivers Gran To AX Circuit Compatibility Resolution Transmission Speed Compression Method Reception Features PAPER HANDLING Recommended Paper Size Paper Input Capacity Paper Output Capacity Paper Weight COLOGY Dimensions (W x D x H) Weight Power Consumption (Max) Ready Mode Energy Saver (Sleep)	PSTN V34 (Su Horizontal: 203 Vertical 98 dpi-3.85dots/mm, 196 dp 33.6 Kbps with au MH, MR, I Automatic, Manual, Substitute, Authorised (100 addre Memory backup, Quick dial/speed dial, Direct fax number entry, Dual a adjustment, User parameter settings, User data transfer Transmitter Termi transfer, Double check destination address, Paperless fa A4, B5(JIS), A5, 250 sheets (Bypass: 1sheet 150 sheets 60 to 163 g/m² (Byp 356 mm x 361 mm x 183 mm Less than 7.3 kg 1,104 V 48 W 6 W	Network TWAIN Scan to folder, Scan to searchable PDF, Scan to PDF/A, TWAIN scanning , PBX pper G3) 8 dpi-8dots/mm, oi-7.7dots/mm, 392 dpi-15.4dots/mm tomatic shift down MMR, JBIG sesse), Time stamp printing, Toner saving mode, Duplex ccess, User code, Auto reduction, Summer time, User function key, Clock nal Identification (TTI), Called Subscriber Identification (CSI), All documer ix reception, Universal send—simultaneous fax and scan A6, LT, Executive et), Maximum: 251 sheets 120 sheets ass: 60 to 230 g/m²) 401 mm x 399 mm x 318 mm Less than 11.8 kg V or less
Bundled Drivers Gean To FAX Circuit Compatibility Resolution Fransmission Speed Compression Method Reception Features Other Supported Features PAPER HANDLING Recommended Paper Size Paper Input Capacity Paper Output Capacity Paper Weight COLOGY Dimensions (W x D x H) Weight Power Consumption (Max) Ready Mode Energy Saver (Sleep) Power Source*	PSTN V34 (Su Horizontal: 203 Vertical 98 dpi-3.85dots/mm, 196 dp 33.6 Kbps with au MH, MR, I Automatic, Manual, Substitute, Authorised (100 addre Memory backup, Quick dial/speed dial, Direct fax number entry, Dual a adjustment, User parameter settings, User data transfer Transmitter Termi transfer, Double check destination address, Paperless fa A4, B5(JIS), A5, 250 sheets (Bypass: 1sheet 150 sheets 60 to 163 g/m² (Byp 356 mm x 361 mm x 183 mm Less than 7.3 kg 1,104 V 48 W 6 W	Network TWAIN Scan to folder, Scan to searchable PDF, Scan to PDF/A, TWAIN scanning , PBX pper G3) 8 dpi-8dots/mm, oi-7.7dots/mm, 392 dpi-15.4dots/mm tomatic shift down MMR, JBIG sesse), Time stamp printing, Toner saving mode, Duplex ccess, User code, Auto reduction, Summer time, User function key, Clock nal Identification (TTI), Called Subscriber Identification (CSI), All documer ix reception, Universal send—simultaneous fax and scan A6, LT, Executive et), Maximum: 251 sheets 120 sheets ass: 60 to 230 g/m²) 401 mm x 399 mm x 318 mm Less than 11.8 kg V or less 42 W 6.2 W Hz, 4.6 Amps or less
Bundled Drivers Gran To FAX Circuit Compatibility Resolution Fransmission Speed Compression Method Reception Features Other Supported Features PAPER HANDLING Recommended Paper Size Paper Input Capacity Paper Output Capacity Paper Weight COLOGY Dimensions (W x D x H) Weight Power Consumption (Max) Ready Mode Energy Saver (Sleep) Power Source* Energy Star	PSTN V34 (Su Horizontal: 203 Vertical 98 dpi-3.85dots/mm, 196 dp 33.6 Kbps with au MH, MR, I Automatic, Manual, Substitute, Authorised (100 addre Memory backup, Quick dial/speed dial, Direct fax number entry, Dual a adjustment, User parameter settings, User data transfer Transmitter Termi transfer, Double check destination address, Paperless fa A4, B5(IIS), A5, 250 sheets (Bypass: 1sheet 150 sheets 60 to 163 g/m² (Byp 356 mm x 361 mm x 183 mm Less than 7.3 kg 1,104 V 48 W 6 W 220 - 240 V, 50/60 N Energy	Network TWAIN Scan to folder, Scan to searchable PDF, Scan to PDF/A, TWAIN scanning , PBX per G3) dipi-8dots/mm, pi-7.7dots/mm, 392 dpi-15.4dots/mm tomatic shift down MMR, JBIG sess), Time stamp printing, Toner saving mode, Duplex ccess, User code, Auto reduction, Summer time, User function key, Clock nal Identification (TTI), Called Subscriber Identification (CSI), All documer ix reception, Universal send—simultaneous fax and scan A6, LT, Executive ett), Maximum: 251 sheets 120 sheets ass: 60 to 230 g/m²) 401 mm x 399 mm x 318 mm Less than 11.8 kg V or less 42 W 6.2 W Hz, 4.6 Amps or less Star v2.0
Bundled Drivers GCAX Circuit Compatibility Resolution Fransmission Speed Compression Method Reception Features Other Supported Features Paper Input Capacity Paper Input Capacity Paper Weight COLOGY Dimensions (W x D x H) Weight Power Consumption (Max) Ready Mode Energy Saver (Sleep) Power Source* Energy Star Green Labels	PSTN V34 (Su Horizontal: 203 Vertical 98 dpi-3.85dots/mm, 196 dp 33.6 Kbps with au MH, MR, I Automatic, Manual, Substitute, Authorised (100 addre Memory backup, Quick dial/speed dial, Direct fax number entry, Dual a adjustment, User parameter settings, User data transfer Transmitter Termi transfer, Double check destination address, Paperless fa A4, B5(IIS), A5, 250 sheets (Bypass: 1sheet 150 sheets 60 to 163 g/m² (Byp 356 mm x 361 mm x 183 mm Less than 7.3 kg 1,104 V 48 W 6 W 220 - 240 V, 50/60 N Energy	Network TWAIN Scan to folder, Scan to searchable PDF, Scan to PDF/A, TWAIN scanning , PBX pper G3) 8 dpi-8dots/mm, oi-7.7dots/mm, 392 dpi-15.4dots/mm tomatic shift down MMR, JBIG sesse), Time stamp printing, Toner saving mode, Duplex ccess, User code, Auto reduction, Summer time, User function key, Clock nal Identification (TTI), Called Subscriber Identification (CSI), All documer ix reception, Universal send—simultaneous fax and scan A6, LT, Executive et), Maximum: 251 sheets 120 sheets ass: 60 to 230 g/m²) 401 mm x 399 mm x 318 mm Less than 11.8 kg V or less 42 W 6.2 W Hz, 4.6 Amps or less
Bundled Drivers Gran To AX Circuit Compatibility Resolution Gransmission Speed Compression Method Reception Features Other Supported Features CAPER HANDLING Recommended Paper Size Paper Input Capacity Paper Untur Capacity Paper Weight COLOGY Dimensions (W x D x H) Weight Power Consumption (Max) Ready Mode Energy Saver (Sleep) Power Source* Energy Star Green Labels CONSUMABLES	PSTN V34 (Su Horizontal: 203 Vertical 98 dpi-3.85dots/mm, 196 dp 33.6 Kbps with au MH, MR, I Automatic, Manual, Substitute, Authorised (100 addre Memory backup, Quick dial/speed dial, Direct fax number entry, Dual a adjustment, User parameter settings, User data transfer Transmitter Termi transfer, Double check destination address, Paperless fa A4, B5(IIS), A5, 250 sheets (Bypass: 1sheet 150 sheets 60 to 163 g/m² (Byp 356 mm x 361 mm x 183 mm Less than 7.3 kg 1,104 V 48 W 6 W 220 - 240 V, 50/60 N Energy: Blue Angel Mark (BAM), Hor	Network TWAIN Scan to folder, Scan to searchable PDF, Scan to PDF/A, TWAIN scanning , PBX pper G3) dipi-8dots/mm, pi-7-7dots/mm, 392 dpi-15.4dots/mm tomatic shift down MMR, JBIG sesse), Time stamp printing, Toner saving mode, Duplex ccess, User code, Auto reduction, Summer time, User function key, Clock nal Identification (TTI), Called Subscriber Identification (CSI), All documer ix reception, Universal send—simultaneous fax and scan A6, LT, Executive et), Maximum: 251 sheets 120 sheets ass: 60 to 230 g/m²) 401 mm x 399 mm x 318 mm Less than 11.8 kg V or less 42 W 6.2 W Hz, 4.6 Amps or less Star v2.0 ng Kong Energy Saving Label
Bundled Drivers Gran To FAX Circuit Compatibility Resolution Fransmission Speed Compression Method Reception Features Other Supported Features Paper Input Capacity Paper Output Capacity Paper Output Capacity Dimensions (W x D x H) Weight Power Consumption (Max) Ready Mode Energy Saver (Sleep) Power Source* Energy Star Green Labels CONSUMABLES Foner Cartridges (K) (Regular Yield)	PSTN V34 (Su Horizontal: 203 Vertical 98 dpi-3.85dots/mm, 196 dp 33.6 Kbps with au MH, MR, I Automatic, Manual, Substitute, Authorised (100 addre Memory backup, Quick dial/speed dial, Direct fax number entry, Dual a adjustment, User parameter settings, User data transfer Transmitter Termi transfer, Double check destination address, Paperless fa A4, B5(JIS), A5, 250 sheets (Bypass: 1sheet 150 sheets 60 to 163 g/m² (Byp 356 mm x 361 mm x 183 mm Less than 7.3 kg 1,104 V 48 W 6 W 220 - 240 V, 50/60 R Energy: Blue Angel Mark (BAM), Hor	Network TWAIN Scan to folder, Scan to searchable PDF, Scan to PDF/A, TWAIN scanning , PBX per G3) dipi-8dots/mm, pi-7-7dots/mm, 392 dpi-15.4dots/mm tomatic shift down MMR, JBIG sess), Time stamp printing, Toner saving mode, Duplex ccess, User code, Auto reduction, Summer time, User function key, Clock nal Identification (TTI), Called Subscriber Identification (CSI), All documer ix reception, Universal send—simultaneous fax and scan A6, LT, Executive et), Maximum: 251 sheets 120 sheets lass: 60 to 230 g/m²) 401 mm x 399 mm x 318 mm Less than 11.8 kg V or less 42 W 6.2 W Hz, 4.6 Amps or less Star v2.0 ng Kong Energy Saving Label k. 1,200 pages
Bundled Drivers GCAX Circuit Compatibility Resolution Fransmission Speed Compression Method Reception Features Other Supported Features Other Supported Features Paper Input Capacity Paper Untput Capacity Dimensions (W x D x H) Weight Cower Consumption (Max) Ready Mode Energy Saver (Sleep) Power Source* Energy Star Green Labels CONSUMABLES Foner Cartridges (K) (Regular Yield) Foner Cartridges (K) (Regular Yield) Foner Cartridges (K) (Righ Yield)	PSTN V34 (Su Horizontal: 203 Vertical 98 dpi-3.85dots/mm, 196 dp 33.6 Kbps with au MH, MR, I Automatic, Manual, Substitute, Authorised (100 addre Memory backup, Quick dial/speed dial, Direct fax number entry, Dual a adjustment, User parameter settings, User data transfer Transmitter Termi transfer, Double check destination address, Paperless fa A4, B5(JIS), A5, 250 sheets (Bypass: 1sheet 150 sheets 60 to 163 g/m² (Byp 356 mm x 361 mm x 183 mm Less than 7.3 kg 1,104 V 48 W 6 W 220 - 240 V, 50/60 R Energy: Blue Angel Mark (BAM), Hor	Network TWAIN Scan to folder, Scan to searchable PDF, Scan to PDF/A, TWAIN scanning , PBX pper G3) dipi-8dots/mm, pi-7.7dots/mm, 392 dpi-15.4dots/mm tomatic shift down MMR, JBIG sesse), Time stamp printing, Toner saving mode, Duplex ccess, User code, Auto reduction, Summer time, User function key, Clock nal Identification (TTI), Called Subscriber Identification (CSI), All documer ix reception, Universal send—simultaneous fax and scan A6, LT, Executive et), Maximum: 251 sheets 120 sheets ass: 60 to 230 g/m²) 401 mm x 399 mm x 318 mm Less than 11.8 kg V or less 42 W 6.2 W Hz, 4.6 Amps or less Star v2.0 ng Kong Energy Saving Label
Bundled Drivers Gran To FAX Circuit Compatibility Resolution Fransmission Speed Compression Method Reception Features Other Supported Features Paper Mandel Paper Size Paper Input Capacity Paper Output Capacity Paper Weight ECOLOGY Dimensions (W x D x H) Weight Power Consumption (Max) Ready Mode Energy Saver (Sleep) Power Source* Energy Star Green Labels CONSUMABLES	PSTN V34 (Su Horizontal: 203 Vertical 98 dpi-3.85dots/mm, 196 dp 33.6 Kbps with au MH, MR, I Automatic, Manual, Substitute, Authorised (100 addre Memory backup, Quick dial/speed dial, Direct fax number entry, Dual ar adjustment, User parameter settings, User data transfer Transmitter Termi transfer, Double check destination address, Paperless fa A4, B5(JIS), A5, 250 sheets (Bypass: 1sheet 150 sheets 60 to 163 g/m² (Byp 356 mm x 361 mm x 183 mm Less than 7.3 kg 1,104 V 48 W 6 W 220 - 240 V, 50/60 R Energy: Blue Angel Mark (BAM), Hore	Network TWAIN Scan to folder, Scan to searchable PDF, Scan to PDF/A, TWAIN scanning , PBX per G3) dipi-8dots/mm, pi-7-7dots/mm, 392 dpi-15.4dots/mm tomatic shift down MMR, JBIG sess), Time stamp printing, Toner saving mode, Duplex ccess, User code, Auto reduction, Summer time, User function key, Clock nal Identification (TTI), Called Subscriber Identification (CSI), All document acception, Universal send—simultaneous fax and scan A6, LT, Executive et), Maximum: 251 sheets 120 sheets lass: 60 to 230 g/m²) 401 mm x 399 mm x 318 mm Less than 11.8 kg V or less 42 W 6.2 W Hz, 4.6 Amps or less Star v2.0 ng Kong Energy Saving Label k. 1,200 pages
Bundled Drivers GCAX Circuit Compatibility Resolution Fransmission Speed Compression Method Reception Features Other Supported Features Other Supported Features Paper Input Capacity Paper Untput Capacity Dimensions (W x D x H) Weight Cower Consumption (Max) Ready Mode Energy Saver (Sleep) Power Source* Energy Star Green Labels CONSUMABLES Foner Cartridges (K) (Regular Yield) Foner Cartridges (K) (Regular Yield) Foner Cartridges (K) (Righ Yield)	PSTN V34 (Su Horizontal: 203 Vertical 98 dpi-3.85dots/mm, 196 dp 33.6 Kbps with au MH, MR, I Automatic, Manual, Substitute, Authorised (100 addre Memory backup, Quick dial/speed dial, Direct fax number entry, Dual a adjustment, User parameter settings, User data transfer Transmitter Termi transfer, Double check destination address, Paperless fa A4, B5(JIS), A5, 250 sheets (Bypass: 1sheet 150 sheets 60 to 163 g/m² (Byp 356 mm x 361 mm x 183 mm Less than 7.3 kg 1,104 V 48 W 6 W 220 - 240 V, 50/60 B Energy Blue Angel Mark (BAM), Hore Black: Approx Approx. 12	Network TWAIN Scan to folder, Scan to searchable PDF, Scan to PDF/A, TWAIN scanning , PBX per G3) dipi-8dots/mm, pi-7-7dots/mm, 392 dpi-15.4dots/mm tomatic shift down MMR, JBIG sesses), Time stamp printing, Toner saving mode, Duplex ccess, User code, Auto reduction, Summer time, User function key, Clock nal Identification (TTI), Called Subscriber Identification (CSI), All document acception, Universal send—simultaneous fax and scan A6, LT, Executive et), Maximum: 251 sheets 120 sheets lass: 60 to 230 g/m²) 401 mm x 399 mm x 318 mm Less than 11.8 kg V or less 42 W 6.2 W d.2, 4.6 Amps or less Star v2.0 ng Kong Energy Saving Label k. 1,200 pages k. 3,000 pages





20W Pasir Panjang Road #04-28 Mapletree Business City Singapore 117439

Phone: +65 6474 0777 Email: sales@ricoh.sg Fax: +65 6476 0777 Website: www.ricoh.sg







